

ASSEMBLING & INSTALLATION INSTRUCTIONS PRODUCT# 2175 2176 2184 2185

For Ceiling Mount Light Fixture



WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .

MOUNTING THE FIXTURE (Fig.1)

1. Shut off the power at the circuit breaker box. Remove old fixture and all hardware from Junction Box.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
3. Attach the crook crossbar(A) to the Junction Box with the two box screws as shown. The side of the cross bar marked "GND" must face out.
4. While holding the fixture body(C) towards the ceiling, connect the electrical wires as Shown in Fig.2, making sure that all wire nuts are secured. You may have to wrap the connections with electrical tape. If your outlet has a ground wire (green or bare copper), connect the fixture ground wire to it. Otherwise connect fixture's ground wire directly to the Mounting strap with the green screw provided. After wires are connected, tuck them carefully inside the Junction Box.
5. Raise fixture body (C) onto the junction box, aligning screws on crook crossbar with mounting holes in fixture body and lock it securely with the hand screw(B).
6. Attach the candela sleeve (D) to the lamp holder.
7. Install the light bulbs in accordance with the fixture's specifications. **NOTE: DO NOT EXCEED THE SPECIFIED WATTAGE.**

Your installation is now complete. Return power to the junction box and test the fixture.

Fig.1



2184 2175

MIN 90°C SUPPLY CONDUCTORS

Fig.2

